

RICHLAND COUNTY GEODETIC SURVEY MARKER

OHIO NORTH ZONE (3401)

POINT NUMBER: 7431A

R/T/S: 17-24-31 Weller

STATION NAME: 67

TYPE OF MARK: Brass Disk in Pavement

SET BY: County - MC

STAMPING ON MARK: GPS STATION RICHLAND COUNTY

DATE SET: 1995.

METHOD OF SURVEY: GPS

FILE: 1995 Report, 2003 Report

COORDINATES BY: Geometrics

LOCATION: The station is located in Richland County, Ohio about 5 mile(s) NE of the City of Mansfield. To reach the station from the intersection of S.R. 603 and US 42 proceed SW along US 42, 0.7 mile(s) to its intersection with TR1688(Windsor Rd) Turn right and proceed west along Windsor Rd, 1.3 mile(s) to its intersection with Cotter Rd. Turn right and proceed North along Cotter Rd, 0.9 mile(s) to its intersection with Pavonia Rd. Turn left and proceed South along Pavonia Rd, 0.2 mile(s). The station is on the right.



HORIZONTAL DATUM: NAD 83 (86)	HORIZONTAL ORDER: 2nd Class II
LATITUDE: 40 49 09.23834 N	LONGITUDE: 082 26 09.11999 W
SPC NORTH: 419912.659 US ft.	SPC EAST: 1986250.312 US ft.
SPC NORTH: 127989.635 m	SPC EAST: 605410.306 m
VERTICAL DATUM: NAVD88	VERTICAL ORDER: 3rd
ELEVATION (METERS): 329.078	ELEVATION (US FT.): 1079.649
HORIZONTAL DATUM: NAD 83 (95)	HORIZONTAL ORDER: 2nd Class II
LATITUDE: 40 49 09.23535 N	LONGITUDE: 082 26 09.11042 W
SPC NORTH: 419912.358 US ft.	SPC EAST: 1986251.048 US ft.
SPC NORTH: 127989.543 m	SPC EAST: 605410.530 m
COMBINED FACTOR: 0.99990225	
Notes:	

RICHLAND COUNTY CONTROL POINTS

AERIAL VIEW 2005



STATION SKETCH

